

BOWLER QUADRO



view



1 [Bowler Quadro 400mm](#)

2 [Bowler Quadro 600mm](#)

3 [Bowler Quadro 800mm](#)

4 [Bowler Quadro 1000mm](#)

size

BOWLER QUADRO

Outdoor LED lighting.

The luminaire has an ergonomic and convenient design, and is suitable for accentual lighting.

Suitable for use as outdoor lighting. The driver and the power supply are located inside the housing.

Housing:	Pressure die-cast aluminum alloy with polyester powder paint
Housing color:	Black, Grey
Glass:	Tempered glass
Beam angle:	100°
Color temperature:	3000K, 4000K, 6000K
Control system:	On/Off
Color rendering index:	CRI >80
Input voltage:	220 V
IES protection classes:	Class I
Impact protection rating:	IK08
Protection Rating:	IP65
Operating temperature:	-40°C ~ +50°C
Weight:	3 – 3.9 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
69503210	Bowler Quadro 400mm 7W 220V IP65	7 W	160×160×400	220 V	100°	3000K, 4000K, 6000K	3
69503185	Bowler Quadro 600mm 15W 220V IP65	15 W	160×160×600	220 V	100°	3000K, 4000K, 6000K	3.3
69503200	Bowler Quadro 800mm 15W 220V IP65	15 W	160×160×800	220 V	100°	3000K, 4000K, 6000K	3.7
69503190	Bowler Quadro 1000mm 15W 220V IP65	15 W	160×160×1000	220 V	100°	3000K, 4000K, 6000K	3.9