

view



RAL

1 [BRUMI-W](#)

2 [BRUMI-G 265](#)

3 [BRUMI-G 650](#)

size

# BRUMI

LED outdoor lighting. The luminaire has an ergonomic and convenient design, and is suitable for accentual lighting.

Suitable for use as outdoor lighting. The driver and the power supply are located inside the housing.

<b>Housing:</b>	Pressure die-cast aluminum alloy with polyester powder paint. Body and glass are fitted with silicone sealants.
<b>Housing color:</b>	Black, Grey, RAL
<b>Glass:</b>	Tempered glass, 3.0 mm
<b>Beam angle:</b>	80°
<b>Color temperature:</b>	3000K, 4000K, 5000K
<b>Control system:</b>	On/Off
<b>Input voltage:</b>	220 V
<b>IES protection classes:</b>	Class I
<b>Protection Rating:</b>	IP 65
<b>Operating temperature:</b>	-40°C ~ +50°C
<b>Weight:</b>	1.4 – 2.75 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
69503250	BRUMI G 265 15W 220V IP65	15 W	Ø120×265	220 V	80°	3000K, 4000K, 5000K	1.4
69503260	BRUMI G 650 15W 220V IP65	15 W	Ø120×650	220 V	80°	3000K, 4000K, 5000K	2.75
69503240	BRUMI W 15W 220V IP65	15 W	Ø120×181×260	220 V	80°	3000K, 4000K, 5000K	1.88