

view



size

1 DIVE XS

2 DIVE S

3 DIVE M

4 DIVE L

5 DIVE XL

6 Mounting bracket

7 Aluminum reflector

8 Safety rope

DIVE

Industrial pendant LED luminaire

Housing:	Die-cast aluminum alloy
Housing color:	Black
Mounting options:	Bracket, Ring
Beam angle:	60°, 90°, 120°
Color temperature:	3000K, 4000K, 5000K, 5700K, 6500K
Control system:	On/Off, 1-10V, DALI
Color rendering index:	CRI >80
Input voltage:	220 V
IES protection classes:	Class I
Impact protection rating:	IK08
Protection Rating:	IP65
Operating temperature:	−40°C ~ +50°C
Weight:	2 – 4.5 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
753020010	DIVE XS 100W 220V IP65	100 W	Ø237×109	220 V	60°, 90°, 120°	3000K, 4000K, 5000K, 5700K, 6500K	2
753020015	DIVE S 150W 220V IP65	150 W	Ø260×111	220 V	60°, 90°, 120°	3000K, 4000K, 5000K, 5700K, 6500K	2.3
753020020	DIVE M 200W 220V IP65	200 W	Ø306×122	220 V	60°, 90°, 120°	3000K, 4000K, 5000K, 5700K, 6500K	3
753020024	DIVE L 240W 220V IP65	240 W	Ø362×127	220 V	60°, 90°, 120°	3000K, 4000K, 5000K, 5700K, 6500K	3.7
753020030	DIVE XL 300W 220V IP65	300 W	Ø408×132	220 V	60°, 90°, 120°	3000K, 4000K, 5000K, 5700K, 6500K	4.5
753020001	Aluminum reflector			220 V			2
753020003	Bracket			220 V			2
753020005	Safety rope			220 V			2