

view



RAL

size

FINLER

Street lighting for city parks, squares, walking areas and car parks

Housing:	Pressure die-cast aluminum alloy with polyester powder paint
Housing color:	Black, Grey, RAL
Mounting:	Ø94 mm
Beam angle:	90°, 130°, Road Type
Color temperature:	3000K, 4000K, 5000K
Control system:	On/Off
Color rendering index:	CRI >70
Input voltage:	220 V,
IES protection classes:	Class I, Class III (SELV)
Protection Rating:	IP66
Operating temperature:	-40°C ~ +50°C
Weight:	0 – 7 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
756030020	Finler 30W 220V IP66	30 W	Ø200×630	220 V	90°, 130°, Road Type	3000K, 4000K, 5000K	7
756045020	Finler 45W 220V IP66	45 W	Ø200×630	220 V	90°, 130°, Road Type	3000K, 4000K, 5000K	7
756050020	Finler 50W 220V IP66	50 W	Ø200×630	220 V	90°, 130°, Road Type	3000K, 4000K, 5000K	7
756060020	Finler 60W 220V IP66	60 W	Ø200×630	220 V	90°, 130°, Road Type	3000K, 4000K, 5000K	7
756080020	Finler 80W 220V IP66	80 W	Ø200×630	220 V	90°, 130°, Road Type	3000K, 4000K, 5000K	7
756002055	Finler diffuser		Ø630				