

GARNET GLOW XS



view



RAL

1 bracket

2 base

3 pipe mount

4 bracket to pipe

5 wrap-around bracket

6 spike

size



GARNET GLOW XS

Multifunctional spotlight for accent lighting.

Multichip 4-in-1 RGB+W Tunable White with DMX-512 operated

Housing:	Pressure die-cast aluminum alloy with polyester powder paint
Housing color:	Black, Grey, RAL
Mounting:	Stainless steel
Beam angle:	2.6°, 3.5°, 12°, 15°, 20°, 30°, 60°, 5°×20, 10°×70, 15°×60, 15°×60°
Color temperature:	2700K, 3000K, 4000K, 5000K, RGBW, 1800K–6000K Tunable White, Tunable White
Control system:	On/Off, 1–10V, DMX-512, DALI
Input voltage:	24 V, 220 V
IES protection classes:	Class I, Class III (SELV)
Protection Rating:	IP66
Operating temperature:	–40°C ~ +50°C
Weight:	1.7 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
622009010	GARNET GLOW XS 9W 100V-264V IP66 Single Color	9 W	158×173×133	220 V	2.6°, 3.5°, 12°, 20°, 30°, 60°, 10°×70, 5°×20	2700K, 3000K, 4000K, 5000K	1.7
622009020	GARNET GLOW XS 9W DC24V RGBW 4in1 IP66	9 W	158×173×133	24 V	15°, 20°, 30°, 15°×60	RGBW	1.7
622015010	GARNET GLOW XS 15W 100V-264V IP66 Single Color	15 W	158×173×133	220 V	2.6°, 3.5°, 12°, 20°, 30°, 60°, 10°×70, 5°×20	2700K, 3000K, 4000K, 5000K	1.7
622015020	GARNET GLOW XS 15W DC24V RGBW 4in1 IP66	15 W	158×173×133	24 V	15°, 20°, 30°, 15°×60°	RGBW	1.7
622020010	GARNET GLOW XS 20W 100V-264V IP66 Single Color	20 W	158×173×133	220 V	2.6°, 3.5°, 12°, 20°, 30°, 60°, 10°×70, 5°×20	2700K, 3000K, 4000K, 5000K	1.7
622020025	GARNET GLOW XS 20W DC24V IP66 DMX Tunable white 1800K - 6000K	20 W	158×173×133	24 V	2.6°, 3.5°, 12°, 20°, 30°, 60°, 10°×70, 5°×20	1800K–6000K Tunable White	1.7
622020020	GARNET GLOW XS 20W DC24V RGBW 4in1 IP66	20 W	158×173×133	24 V	15°, 20°, 30°, 15°×60°	RGBW	1.7