

view



RAL

1 JONGLA

2 JONGLA DOUBLE

size

JONGLA

Street lighting for city parks, squares, walking areas and car parks

Housing:	Pressure die-cast aluminum alloy with polyester powder paint
Housing color:	Black, RAL
Mounting:	Ø76 mm
Beam angle:	120°
Color temperature:	2700K, 3000K, 4000K, 5000K
Control system:	On/Off
Input voltage:	220 V
IES protection classes:	Class I
Protection Rating:	IP66
Operating temperature:	-40°C ~ +50°C
Weight:	10 – 29 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
748050010	JONGLA 50W single color 220V IP66	50 W	Ø600×610	220 V	120°	2700K, 3000K, 4000K, 5000K	10
748080010	JONGLA 80W single color 220V IP66	80 W	Ø600×610	220 V	120°	2700K, 3000K, 4000K, 5000K	10
748100010	JONGLA 100W single color 220V IP66	100 W	Ø600×610	220 V	120°	2700K, 3000K, 4000K, 5000K	10
748050015	JONGLA SINGLE 50W single color 220V IP66	50 W	Ø600×610	220 V	120°	2700K, 3000K, 4000K, 5000K	12
748080015	JONGLA SINGLE 80W single color 220V IP66	80 W	Ø600×610	220 V	120°	2700K, 3000K, 4000K, 5000K	12
748100015	JONGLA SINGLE 100W single color 220V IP66	100 W	Ø600×610	220 V	120°	2700K, 3000K, 4000K, 5000K	12
748050020	JONGLA DOUBLE 2x50W single color 220V IP66	50 W x2	1630×610×600	220 V	120°	2700K, 3000K, 4000K, 5000K	29
748080020	JONGLA DOUBLE 2x80W single color 220V IP66	80 W x2	1630×610×600	220 V	120°	2700K, 3000K, 4000K, 5000K	29
748100020	JONGLA DOUBLE 2x100W single color 220V IP66	100 W x2	1630×610	220 V	120°	2700K, 3000K, 4000K, 5000K	29