

view



1 OMI XS

2 OMI S

3 OMI M

4 OMI L

size

OMI

Floodlight for landscape and architectural lighting

Housing:	Die-casting powder coated aluminum
Housing color:	Black, Grey, White, RAL
Gasket:	Tooling shaped double silicone seal
Beam angle:	4°, 5°, 8°, 10°, 12°, 15°, 20°, 25°, 30°, 40°, 45°, 60°, 10°×22°, 10°×30°, 15°×55°, 20°×60°
Color temperature:	2700K, 3000K, 4000K, 6000K, RGBW, Tunable White
Control system:	On/Off, PWM, 0-10V, DALI, DMX-512
Color rendering index:	CRI >80
Input voltage:	24 V, 220 V
IES protection classes:	Class I, Class III (SELV)
Protection Rating:	IP66
Operating temperature:	-40°C ~ +50°C
Weight:	0.5 – 1.5 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
70101002	OMI XS 5W 24V IP66 SINGLE	5 W	Ø45×89	24 V	5°, 8°, 10°, 12°, 20°, 25°, 30°, 40°, 45°, 60°, 10°×22°, 15°×55°, 20°×60°	2700K, 3000K, 4000K, 6000K	0.5
70101004	OMI S 7W 220V IP66 SINGLE	7 W	Ø56×100	220 V	4°, 8°, 15°, 25°, 30°, 45°, 60°, 10°×30°	2700K, 3000K, 4000K, 6000K	0.7
70101010	OMI S 4W 24V IP66 RGBW DMX-512	4 W	Ø56×100	24 V	15°, 25°, 60°	RGBW	0.7
70101012	OMI M 10W 220V IP66 SINGLE	10 W	Ø69×110	220 V	5°, 8°, 10°, 12°, 20°, 25°, 30°, 40°, 45°, 60°, 10°×22°, 15°×55°, 20°×60°	2700K, 3000K, 4000K, 6000K	0.9
70101018	OMI M 15W 24V IP66 RGBW DMX-512	15 W	Ø69×110	24 V	15°, 25°, 40°, 60°	RGBW	0.9
70101020	OMI L 12W 24V/220V IP66 SINGLE	12 W	Ø88×145	220 V	5°, 8°, 10°, 12°, 20°, 25°, 30°, 40°, 45°, 60°, 10°×22°, 15°×55°, 20°×60°	2700K, 3000K, 4000K, 6000K	1.5
70101026	OMI L 18W 24V IP66 RGBW DMX-512	18 W	Ø88×145	24 V	15°, 25°, 40°, 60°	RGBW	1.5