

view



RAL

1 base

2 spike

3 bracket to pipe

size

GLOWHEAD XS

Multifunctional floodlight with tiny size

Housing:	Pressure die-cast aluminum alloy with polyester powder paint
Housing color:	Black, Grey, RAL
Beam angle:	2.5°, 6°, 9°, 12°, 15°, 20°, 30°, 45°, 60°, 5°×20°, 10°×70°, 15°×60°
Color temperature:	2700K, 3000K, 4000K, 5000K, 5700K, Red, Green, Blue, RGBW
Control system:	On/Off, DMX-512, 0-10V, DALI
Input voltage:	12 V, 24 V, 220 V
IES protection classes:	Class I, Class III (SELV)
Protection Rating:	IP66
Operating temperature:	-40°C ~ +50°C
Weight:	1 kg

Article	Name	Power	Dimensions, mm	Input voltage	Beam angle	Color temperature	Weight, kg
622201150	GLOWHEAD XS 10W 220V SINGLE IP66	10 W	100×178×160	220 V	2.5°, 6°, 12°, 20°, 30°, 45°, 60°, 10°×70°, 5°×20°	2700K, 3000K, 4000K, 5000K, 5700K, Red, Green, Blue	1
622201152	GLOWHEAD XS 15W 12V/24V DMX-512 RGBW 4in1 IP66	15 W	100×178×160	12 V, 24 V	9°, 15°, 20°, 30°, 45°, 15°×60°	RGBW	1